

PERMISSIBLE MAXIMUM DIMENSIONS IN EUROPE					
COUNTRY	HEIGHT	WIDTH	LENGTH		
			Lorry or Trailer	Road Train	Articulated Vehicle
Albania					
Austria	4 m	2,55 m (2)	12 m	18,75 m	16,50 m
Azerbaijan	4 m	2,55 m	12 m	20 m	20 m
Belarus	4 m	2,60 m	12 m	18 m	20 m
Belgium	4 m (1)	2,55 m (2)	12 m	18,75 m	16,50 m
Bosnia-Herzegovina					
Bulgaria	4 m	2,50 m	12 m	18,75 m	16,50 m
Croatia	4 m	2,60 m	12 m	18,35 m	16,50 m
Czech Republic	4 m	2,55 m	12 m	18,75 m	16,50 m
Denmark	4 m	2,55 m (2)	12 m	18,75 m	16,50 m
Estonia	4 m	2,55 m	12 m	18,75 m	16,50 m
Finland	4,20 m	2,55 m (2)	12,50 m	25,25 m	16,50 m
France	not defined	2,55 m (2)	12 m	18,75 m	16,50 m
FYR Macedonia					
Georgia	4 m	2,50 m	12 m	20 m	20 m
Germany	4 m	2,55 m (2)	12 m	18,75 m	16,50 m
Greece	4 m	2,55 m (2)	12 m	18,75 m	16,50 m
Hungary	4 m	2,55 m	12 m	18,75 m	16,50 m
Iceland	4,20 m	2,55 m	12 m	22 m (9)	18 m
Ireland	4 m	2,55 m (2)	12 m	18,35 m	16,50 m
Italy	4 m (5)	2,55 m (2)	12 m	18,75 m	16,50 m
Latvia	4 m	2,55 m	12 m	18,75 m	16,50 m
Liechtenstein	4 m	2,55 m	12 m	18,75 m	16,50 m
Lithuania	4 m	2,55 m	12 m	18,75 m	16,50 m
Luxembourg	4 m	2,55 m (2)	12 m	18,75 m	16,50 m
Moldova	4 m	2,50 m (2)	12 m	20 m	16,50 m
Netherlands	4 m	2,55 m (2)	12 m	18,75 m	16,50 m
Norway	not defined	2,55 m	12 m (6)	18,75 m	16,50 m (7)
Poland	4 m	2,55 m	12 m	18,75 m	16,50 m
Portugal	4 m	2,55 m (2)	12 m	18,75 m	16,50 m
Romania	4 m	2,50 m	12 m	18,35 m	16,50 m
Russia	4 m	2,50 m	12 m	20 m	20 m
Slovakia	4 m	2,55 m	12 m	18,75 m	16,50 m
Slovenia	4 m		12 m	18,75 m	16,50 m
Spain	4 m	2,55 m (2) (3)	12 m	18,75 m (4)	16,50 m
Sweden		2,60 m	12 m	24 m	24 m
Switzerland	4 m	2,55 m (8)	12 m	18,75 m	16,50 m
Turkey	4 m	2,55 m	12 m	18,75 m	16,50 m
Ukraine					
United Kingdom	not mandatory	2,55 m (2)	12 m	18,75 m	16,50 m
Yugoslavia					

- height margin = + 1%
- refrigerated vehicles = 2,60 m
- vehicles equipped with permanent superstructure = 2,60 m
- transport of vehicles = 18,75 m unloaded; 20,55 loaded
- transport of vehicles = 4,20m ; Transport of containers or livestock = 4,30 m
- lorries or trailers registered before 17 Sept. 1997 = 12,40 m. Regulation valid until 1 January 2007
- articulated vehicles registered before 17 Sept. 1997 = 17 m. Regulation valid until 1 January 2007
- 2,60m for veh. with fixed or mobile superstructure adapted to refrigerated transport and with side-wall depth, including insulation, of 45 mm at least
- 25,25 m in special cases: when deemed economical compared with usual transport; conditions regarding time of year and weekdays; only on certain roads